


VEHICLE TESTING TECHNOLOGY

TPS II EURO VP 440003



SPEEDOMETER TESTER



TPS II EURO

VP 440003

The TPS II EURO speedometer test bench is perfect for assessing deviations in the speedometer speed of cars and trucks of up to 13.0 t. The speedometer test can be performed with up to ten freely selectable test points. In addition, the distance measurement can be performed with up to ten freely selectable test points. With the hydraulic lifting bar as an exit aid for the drive axle, a problem-free test sequence is always guaranteed.

PRODUCT DETAILS/ACCESSORIES

Description:

- Ideal for assessing the variation in Tachometer speed in cars and trucks
- Tachometer testing with up to ten freely selectable test points
- Measurement of distance travelled with up to ten optional test points
- Hydraulic lifting bar as an exiting aid for the drive axle
- · Automatic analysis of:
 - Speed according to tachometer display (V target)
 - Actual speed (V actual)
 - · Deviation in %
 - Max. speed
 - Distance travelled (remote control recommended)

TECHNICAL DATA

Axle load	13000 kg
Min. track	820 mm
Max. track	2620 mm
Roller diameter	318 mm
Roller axle distance	457 mm
Roller length	900 mm
Drive power (hydraulic unit)	2.5 kW
Operating pressure (lifting bar)	105 bar
Lifting bar lifting power	10 t
Hydraulic fluid quantity f. hyd. unit	51
(included)	
gG fuse	16 A
Power supply	3/N/PE 400 V 50 Hz
Roller set dimensions (H x W x L)	400 x 840 x 3000 mm

ACCESSORIES

VZ 935306	Flame coated load rollers -EXTRA CHARGE	SUPPLEMENTARY CHARGES	
	Adapter Set Continental CTC II / Workshop Tab II -NET-	VT 998271	Transport Werkverkehr -SÜDTachoprüfstand LKW
		VT 998272	New 272 Transport Werkverkehr - NORDTachoprüfstand LKW
VP 186051	Communication Desk EUROSYSTEM Car/Truck (with electronics) Model: MCD 2000		

MAHA Maschinenbau Haldenwang GmbH & Co. KG / Hoyen 20 / 87490 Haldenwang / Germany Phone: +49 8374 585 0 / Fax: +49 8374 585 0 / sales@maha.de / www.maha.de



