



AXLIFT

VP 985058

Axle Jack hydro-pneumatic, with 2600 kg load capacity

DESCRIPTION:

- ♦ with increased cross-beam extension length (925 – 1755 mm)
- ♦ Max. support length 1630 mm in conjunction with support discs (VZ 975644)
- ♦ Powder coating in RAL 7016, anthracite

STANDARD DELIVERY:

- ♦ incl. carriage
 - ♦ incl. air supply set (spiral hose, guide rope)
 - ♦ incl. 2 rubber pads for lifting brackets
 - ♦ incl. 3 lift extenders measuring 10 / 45 / 85 mm
- Minimum clear distance between runway and lift of 950 mm is required!

TECHNICAL DATA:

Load capacity CE	2600 kg
Min. / max. operating pressure	8,5 bar / 12 bar
Minimum air quantity	500 l/min
Full travel	250 mm
Swing arm extension	925 mm - 1755 mm
Protrusion above runway max.	70 mm

ACCESSORIES:

VZ 975587	Support Extension 130 mm (2 pieces)
VZ 975597	Plug-In Type Hard Rubber Chocks
VZ 975598	Lifting saddle for axle lift AL II
VZ 975821	Axle lift carriage
VZ 975822	Axle lift guide rollers
VZ 975644	Support disc height-adjustable 60 mm
VZ 975645	Support Extension 60 mm (2 pieces)
VZ 975646	Rubber Support, Round (2 pieces)
VW 997514	Pack.charges f.A-Jack in case of sep.del.EU
VW 997515	Pack.charges f.A-Jack in case of sep.del.Overseas