



AXPLAY

VP 225004

Axle Play Tester up to 3500 kg axle load

DESCRIPTION:

- ◆ Two test plates installed into foundation at ground level
- ◆ Rapid determination of defects and wear and tear on steering parts, wheel bearings, spring system and suspension
- ◆ Powerful and even movement thanks to hydraulic drive with high precision for quick and easy positioning
- ◆ Low-noise oil-submerged hydraulic unit increases user convenience too
- ◆ On maintenance-free Teflon sliding tracks
- ◆ Counter-set cross and longitudinal movement of the test plates
- ◆ One-hand operation without lifting the vehicle
- ◆ Aluminium cable inspection light with switch for moving the test plates
- ◆ 4-way control with mechanical multi-way valve for controlling the test plate movements

STANDARD DELIVERY:

- ◆ 2 pieces test plates
- ◆ Electrical control box
- ◆ Hydraulic power unit
- ◆ Aluminium cable inspection light
- ◆ Operating manual
- ◆ EC Declaration of Conformity CE

TECHNICAL DATA:

Axle load	3500 kg
Wheel load	1750 kg
Test plate movement	100 mm
Test plate speed	70
Installation depth	175 mm
Maximum thrust per side	11000 N
Operating pressure	120 bar
Motor power	2,5 kW
Fuse gG	16 A
Power supply	3/N/PE 400 V 50 Hz
Dimensions of test plate (L x W x H)	625 mm x 625 mm x 8 mm
Hydraulic fluid quantity (not included in standard delivery)	15 l

ACCESSORIES:

VZ 935088	In-Ground Tub for PMS (2 pcs.)
VZ 935272	In-Ground Tub PMS hot dip galvanized
VM 999005	Hydraulic Oil (HLP-D 32) per litre
VM 999014	Hydraulic Oil (HLP 32) Biodegradable
VM 995129	Install. material PMS/LMS 101 and PMS 3X-PIT
VV 997021	Packing PMS series -Europe-
VV 997224	Packing PMS series -overseas-
VV 997267	Packing PMS/LMS ground tub